



Hydro-Quip, the industry leader in hydrotherapy bath heating technology, introduces the **Pure Heat™ - Universal Series** of in-line bath heaters.

- Suitable for new installation or retrofit.
- A model for every jetted bath application
- UL Standard 1795 compliant.
 - (2) bonding lugs
 - # 8 AWG bonding wire
 - fittings for installation to 3/4", 1" or 1-1/2" PVC plumbing (101 series)
 - fittings for installation to 1-1/2" or 2" PVC plumbing (301 series)
 - Field installation specific installation instructions.
- All models provide the 100% efficiency of Certified Real Heat[™] technology. No alternative bath heating devices compare.
- For "T" shaped pressure side models, 240-volt models, or custom requests visit our web site <u>www.bathheaters.com</u> or call 1-520-887-3424

	SERIES*	GALLONS**	BTU	AMPS	WATTS	#JETS	VOLTS*
SMALL BATH	1000-A	UP TO 40	2224	5.4	650	2-4	120
STANDARD BATH	1000	UP TO 60	3422	8.3	1000	4-6	120
LARGE BATH	1500	UP TO 100	5133	12.5	1500	4-8	120
2-PERSON BATH	1900	UP TO 200	6502	15.8	1900	4-12	120

*Series to gallon comparisons are based on optimal performance. Smaller wattage heaters can be used on larger tubs to slow the rate of heat loss, but may not be able to maintain desired water temperature range.

** To determine gallons measure in ft - length X width X depth (to overflow drain) X 7.5